


6" Coaxial Ceiling Speaker (3.8W-7.5W-15W-30W)**Features:**

- Commercial public address system ceiling speaker with transformer.
- Hi-Fi range coaxial ceiling loudspeaker with fire dome.
- Ideal for school, restaurant, hotel, train station & airport BGM and speech use.
- High power output range in-ceiling speaker for big scale PA system installation.
- Rated power output 3.8W-7.5W-15W-30W at 100V.
- Rated power output of 30W RMS.
- 6" coaxial PP driver unit.
- Line input 100V or 70V & 8Ω.
- ABS enclosure, metal grille and metal back can in white.
- Flush mount in-ceiling quick and secure installation.
- Wide dispersion rang installation PA loudspeaker.


Frequency Response & SPL Diagram:

Description	6" Coaxial Ceiling Speaker
Rated Power Output	3.8W-7.5W-15W-30W
Line Input	100V or 70V & 8Ω
Frequency Response	100-20KHz
SPL(@1W/m)	88dB
Speaker Unit	6" coaxial PP driver unit
Cutout Size	200mm
Dimension	230(D)×150(H)mm
Material	ABS enclosure, metal grille and metal back can in white
Mounting Way	Flush mount in-ceiling quick and secure installation
Weight	2.2kg

Side View & Dimension:

Mounting Guidance:


Frequency Response & SPL Diagrams:



The information provided in this data brochure is correct at the time of printing. All changes or modifications, may then be technical or other, or changes in the availability of products are expressly reserved. No liability will be assumed for printing mistakes and errors. ©isolectra Far East Pte Ltd.