


5 inch Fireproof Wall Mount Speaker (0.75W-1.5W-3W-6W)**Feature:**

- Commercial fireproof wall speaker with transformer.
- Ideal for school, office, hotel and airport voice evacuation and PA system.
- Compliant with the EN54-24 EVAC standard.
- Ceramic connector, fire dome, 95°C fire-resistant cable and thermal fuse.
- Rated power output 0.75W-1.5W-3W-6W at 100V.
- 5" full range paper non-flammable driver unit.
- Line input 100V or 70V with transformer.
- Steel enclosure, steel grille and fire dome in white RAL 7035
- Wall mount or Surface mount and quick installation by screw hole



Specification:

Description	5" Fireproof Wall Mount Speaker
Rated Power Output	0.75W-1.5W-3W-6W
Line Input	100V or 70V
Frequency Response	120-10KHz
SPL(@1W/m)	92dB
Speaker Unit	5" full range paper non-flammable driver unit
Cutout Size	160mm
Dimension	160(W)×160(D) x 60(H) mm
Material	Steel enclosure, Steel grille and fire dome in white RAL 7035
Mounting Way	Quick installation by hanging screw hole
Weight	1kg

Mounting, Dimension & Side View:



Frequency Response & SPL Diagram:



The information provided in this data brochure is correct at the time of printing. All changes or modifications, may then be technical or other, or changes in the availability of products are expressly reserved. No liability will be assumed for printing mistakes and errors. ©isolectra Far East Pte Ltd.