



6 Zone Voice Evacuation Controller



Feature:

- Digital voice evacuation system all in one controller.
- Integration of EVAC controller, paging system, PA system & BGM system together.
- Built-in two separate players for EVAC and alert voice message by SD card.
- Built-in 6 zone AB speaker line low impedance supervision.
- Built-in amplifier auto changeover into standby when fault.
- Capacity of connection 20 units remote microphone.
- Red button EVAC message push to activate with priority except fireman mic.
- 6 zone speaker outputs with separate zone volume control (ATT).
- 6 zone separate indicator for EVAC, fault, music/paging & select.
- System indicators of AC, DC, fault and indicators for EVAC, alert & fireman mic.
- Zone capacity of 120 zones by cascaded 19 units router.
- With 16 programmable control inputs and 16 programmable control outputs for third party system integration.
- With Fault, EVAC outputs and Reset input for third party system integration.
- With fireman microphone of highest priority.
- Priority level: fireman mic, EVAC, input 1, remote microphone, timer & BGM.
- Two combo inputs for mic/line, 4 line inputs and one REC output.
- Two RJ45 ports for router, two RJ45 for remote microphone input and two RJ45 for LAN/WAN/Internet network.
- AC 230V and DC24V battery input. Auto switch into the battery backup when AC fails.

Rear Panel:



Specifications:

Model	EVC500AMP
Description	6 Zone Voice Evacuation Controller
Fireman Microphone	5Mv, 600Ω
Line 1-2 Inputs	385mV, 10kΩbalanced Combo
Line 3-6 Inputs	350mV, 10kΩ, RCA
Frequency Response	80Hz~20kHz
THD	< 1% at RMS, 1KHz
S/N Ratio	>70dB
Line Output	8 outputs
REC Output	200mV
Control Input & Output	16 programmable control inputs: Max 3.3V (voltage mode) or 0V closed contact 16 programmable control outputs: 0V closed contact; Control output for fault & EVAC: 0V closed contact; Reset control input: 0V closed contact
Voice Message	MP3 or WMA format, two separate players of SD card with protection cover, programmable voice message up to 255, 10 years valid
Event Record	HEX format, Hard Flash memory, events up to 1000 records, 10 years valid
Operation Environment	Operation Temp: +5°C ~ +40°C; Store Temp: -20°C ~ +70°C; Operation Humidity: <95%
Power Consumption	60W
Power Supply	AC230V or 115V & DC24V battery inputs, 50-60HZ
AC Fuse	250V/6.3A, slow type and restorable fuse
Dimension	484(W)×132(H)×449(D) mm
Weight	9.5kg

The information provided in this data brochure is correct at the time of printing. All changes or modifications, may then be technical or other, or changes in the availability of products are expressly reserved. No liability will be assumed for printing mistakes and errors. ©isolectra Far East Pte Ltd.

No. 8 Commonwealth Lane #02-04 Singapore 149555, Tel: +65 6272 2371 Fax: +65 6278 9019, Email: enquiry@isolectra.com.sg, website: www.isolectra.com.sg