

6" Ceiling Speaker (1.5W-3W-6W)




Feature:

- ✓ Commercial ceiling speaker with transformer
- ✓ Ideal for school, office, hotel and airport background music system
- ✓ Rated power output 1.5W-3W-6W at 100V
- ✓ 6" full range paper driver unit
- ✓ IP waterproof rate of IP44
- ✓ Ceiling speaker with metal fire dome
- ✓ Line input 100V or 70V
- ✓ Metal enclosure, metal grille and metal back cover in white
- ✓ In-ceiling quick installation by spring clip


Specification:

Description	6" Ceiling Speaker
Rated Power Output	1.5W-3W-6W
Line Input	100V or 70V
Frequency Response	100-18KHz
SPL(@1W/m)	92dB
Speaker Unit	6" full range paper cone
IP Rate	IP44
Cutout Size	175mm
Dimension	200(D)×90(H)mm
Material	Metal enclosure, metal grille and metal back cover in white
Mounting Way	In-ceiling spring clip quick installation
Weight	0.9kg
Packaging	630x430x250mm (12PCS)





Dimension & Side View:



Mounting Guidance:



Frequency Response & SPL Diagram:



The information provided in this data brochure is correct at the time of printing. All changes or modifications, may then be technical or other, or changes in the availability of products are expressly reserved. No liability will be assumed for printing mistakes and errors. ©isolectra Far East Pte Ltd.

No. 8 Commonwealth Lane #02-04 Singapore 149555, Tel: +65 6272 2371 Fax: +65 6278 9019, Email: enquiry@isolectra.com.sg, Website: www.isolectra.com.sg