

5" Fireproof Ceiling Speaker (1.5W-3W-6W)





Feature:

- ✓ Commercial fireproof wall speaker with transformer.
- ✓ Ideal for school, office, hotel and airport voice evacuation and PA system.
- ✓ Compliant with the EN54-24 EVAC standard.
- ✓ Ceramic connector, fire dome, 95°C fire-resistant cable and thermal fuse.
- ✓ Rated power output 1.5W-3W-6W at 100V.
- ✓ 5" full range paper woofer.
- ✓ Line input 100V or 70V with transformer.
- ✓ Metal enclosure, metal grille in white.

Specification:

Description	5" Fireproof Wall Mount Speaker
Rated Power Output	1.5W-3W-6W
Line Input	100V or 70V
Frequency Response	130-15KHz
SPL(@1W/m)	92dB
Speaker Unit	5" full range paper woofer
Cutout Size	160mm
Dimension	180(D)×135(H)mm
Material	Metal enclosure, metal grille in white and fire dome in red
Mounting Way	Quick installation by hanging screw hole
Weight	1kg

Frequency Response & SPL Diagram:



The information provided in this data brochure is correct at the time of printing. All changes or modifications, may then be technical or other, or changes in the availability of products are expressly reserved. No liability will be assumed for printing mistakes and errors. ©isolectra Far East Pte Ltd.

No. 8 Commonwealth Lane #02-04 Singapore 149555, Tel: +65 6272 2371 Fax: +65 6278 9019, Email: enquiry@isolectra.com.sg, Website: www.isolectra.com.sg