

10 Channel Public Address System Monitor Panel



Features:

- ✓ Public address system monitor panel.
- ✓ Design with 10 channel inputs.
- ✓ Built-in 5 Watt @ 8Ω monitor speaker.
- ✓ Built-in monitor speaker to listen and monitor the system output..
- ✓ The monitor speaker with adjustable volume control.
- ✓ Five element LED level meter is provided.
- ✓ With 10 channel selector to choose the supervised output channel.

Specification:

| | |
|------------------------------|--------------------------|
| Description | 10 Channel Monitor Panel |
| Input | 70-100 V, 10kΩ |
| Output | 65dB SPL Variable |
| Frequency Response | 100Hz – 15kHz |
| Signal to Noise Ratio | 80dB |
| Speaker | 5W @ 8 Ω |
| Power Consumption | 10-15Watt |
| Protection | AC fuse |
| Power Requirement | AC 220-240V/50-60 Hz |
| Dimension | 484(W)x350(D)x88(H) mm |
| Weight | 6.3kg |

Rear Panel:



The information provided in this data brochure is correct at the time of printing. All changes or modifications, may then be technical or other, or changes in the availability of products are expressly reserved. No liability will be assumed for printing mistakes and errors. ©isolectra Far East Pte Ltd.

No. 8 Commonwealth Lane #02-04 Singapore 149555, Tel: +65 6272 2371 Fax: +65 6278 9019, Email: enquiry@isolectra.com.sg, Website: www.isolectra.com.sg